

Package: statdecideR (via r-universe)

May 20, 2026

Title Automated Statistical Analysis and Plotting with CLD

Version 0.1.6

Description A lightweight tool that provides a reproducible workflow for selecting and executing appropriate statistical analysis in one-way or two-way experimental designs. The package automatically checks for data normality, conducts parametric (ANOVA) or non-parametric (Kruskal-Wallis) tests, performs post-hoc comparisons with Compact Letter Displays (CLD), and generates publication-ready boxplots, faceted plots, and heatmaps. It is designed for researchers seeking fast, automated statistical summaries and visualization. Based on established statistical methods including Shapiro and Wilk (1965) <doi:10.2307/2333709>, Kruskal and Wallis (1952) <doi:10.1080/01621459.1952.10483441>, Tukey (1949) <doi:10.2307/3001913>, Fisher (1925) <ISBN:0050021702>, and Wickham (2016) <ISBN:978-3-319-24277-4>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Depends R (>= 4.1)

Imports ggplot2, dplyr, agricolae, effectsize, stringr, stats

NeedsCompilation no

Author Subhradip Bhattacharjee [aut, cre] (ORCID: <<https://orcid.org/0000-0003-2330-2979>>), Bappa Das [aut, ctb] (ORCID: <<https://orcid.org/0000-0003-1286-1492>>), Parveen Kumar [aut, ctb] (ORCID: <<https://orcid.org/0000-0001-9352-8303>>), Rakesh Kumar [aut, ctb] (ORCID: <<https://orcid.org/0000-0002-9711-0964>>), Amitava Panja [aut, ctb] (ORCID: <<https://orcid.org/0000-0002-6226-2933>>), Pritam Roy [aut, ctb], Divyacrota Majumder [aut, ctb], Susanta Dutta [aut, ctb] (ORCID: <<https://orcid.org/0000-0003-0885-9744>>), Indian Council of Agricultural Research [cph]

Maintainer Subhradip Bhattacharjee <subhradip25@gmail.com>

Config/pak/sysreqs libicu-dev
Repository https://subhradip25.r-universe.dev
Date/Publication 2025-05-01 10:30:01 UTC
RemoteUrl https://github.com/cran/statdecideR
RemoteRef HEAD
RemoteSha b5318f0bf0953c669da814512c7ef98845c34dd7

Contents

df_nonparam	2
run_statdecide	2

Index	4
--------------	----------

df_nonparam	<i>Example Data for Non-parametric test</i>
-------------	---

Description

An example dataset of pollen collection by honeybee at different times and different months.

Usage

df_nonparam

Format

An object of class `data.frame` with 132 rows and 3 columns.

run_statdecide	<i>Run Statistical Decision Workflow</i>
----------------	--

Description

Automatically checks normality, selects appropriate test (ANOVA or Kruskal-Wallis), performs post-hoc, and visualizes results with compact letter display (CLD). Returns all results as an object with optional console output.

Usage

```
run_statdecide(data, dep_var, group_vars, cld_offset = 5, verbose = TRUE)
```

Arguments

<code>data</code>	A data frame.
<code>dep_var</code>	Character. Name of the dependent variable.
<code>group_vars</code>	Character vector. One or two grouping variables.
<code>cld_offset</code>	Numeric. Vertical offset to place CLD labels above the boxplot (default: 5).
<code>verbose</code>	Logical. Whether to print progress messages and results (default: TRUE).

Value

A list containing:

- normality_test** Results of Shapiro-Wilk test
- main_effects** Results for each main effect
- interaction** Interaction results (if 2 group_vars)
- plots** List of ggplot objects
- facet_plot** Faceted ggplot (if 2 group_vars)
- heatmap** Heatmap ggplot (if 2 group_vars)

Examples

```
# Silent operation
results <- run_statdecide(data = df_nonparam, dep_var = "Pollen",
                        group_vars = c("Month", "Time"), verbose = FALSE)

# With console output
run_statdecide(data = df_nonparam, dep_var = "Pollen", group_vars = "Month")
```

Index

* **datasets**

df_nonparam, [2](#)

df_nonparam, [2](#)

run_statdecide, [2](#)